

NAG Library Function Document

nag_opt_simplex (e04ccc)

1 Purpose

nag_opt_simplex (e04ccc) minimizes a general function $F(x)$ of n independent variables $x = (x_1, x_2, \dots, x_n)^T$ by the Simplex method. No derivatives are required.

2 Specification

```
#include <nag.h>
#include <nage04.h>

void nag_opt_simplex (Integer n,
    void (*funct)(Integer n, const double xc[], double *fc, Nag_Comm *comm),
    double x[], double *fmin, Nag_E04_Opt *options, Nag_Comm *comm,
    NagError *fail)
```

3 Description

nag_opt_simplex (e04ccc) finds an approximation to a minimum of a function $F(x)$ of n variables. You must supply a function to calculate the value of $F(x)$ for any set of values of the variables.

The method is iterative. A simplex of $n + 1$ points is set up in the n -dimensional space of the variables (for example, in two dimensions the simplex is a triangle) under the assumption that the problem has been scaled so that the values of the independent variables at the minimum are of order unity. The starting point you provided is the first vertex of the simplex, the remaining n vertices are generated internally (see Parkinson and Hutchinson (1972)). The vertex of the simplex with the largest function value is reflected in the centre of gravity of the remaining vertices and the function value at this new point is compared with the remaining function values. Depending on the outcome of this test the new point is accepted or rejected, a further expansion move may be made, or a contraction may be carried out. When no further progress can be made the sides of the simplex are reduced in length and the method is repeated.

The method tends to be slow, but it is robust and therefore very useful for functions that are subject to inaccuracies.

4 References

Nelder J A and Mead R (1965) A simplex method for function minimization *Comput. J.* **7** 308–313

Parkinson J M and Hutchinson D (1972) An investigation into the efficiency of variants of the simplex method *Numerical Methods for Nonlinear Optimization* (ed F A Lootsma) Academic Press

5 Arguments

- 1: **n** – Integer *Input*
On entry: n , the number of independent variables.
Constraint: $n \geq 1$.
- 2: **funct** – function, supplied by the user *External Function*
funct must calculate the value of $F(x)$ at any point x . (However, if you do not wish to calculate the value of $F(x)$ at a particular x , there is the option of setting an argument to cause nag_opt_simplex (e04ccc) to terminate immediately.)

The specification of **funct** is:

```
void funct (Integer n, const double xc[], double *fc, Nag_Comm *comm)
```

1: **n** – Integer *Input*

On entry: n , the number of variables.

2: **xc[n]** – const double *Input*

On entry: x , the point at which the value of $F(x)$ is required.

3: **fc** – double * *Output*

On exit: the value of $F(x)$ at the current point x .

4: **comm** – Nag_Comm *

Pointer to structure of type Nag_Comm; the following members are relevant to **funct**.

flag – Integer *Input/Output*

On entry: **comm** → **flag** contains a non-negative number.

On exit: if **funct** resets **comm** → **flag** to some negative number then `nag_opt_simplex (e04ccc)` will terminate immediately with the error indicator `NE_USER_STOP`. If **fail** is supplied to `nag_opt_simplex (e04ccc)`, **fail.errnum** will be set to your setting of **comm** → **comm** → **flag**.

first – Nag_Boolean *Input*

On entry: will be set to `Nag_TRUE` on the first call to **funct** and `Nag_FALSE` for all subsequent calls.

nf – Integer *Input*

On entry: the number of calls made to **funct** so far.

user – double *

iuser – Integer *

p – Pointer

The type Pointer will be `void *` with a C compiler that defines `void *` and `char *` otherwise. Before calling `nag_opt_simplex (e04ccc)` these pointers may be allocated memory and initialized with various quantities for use by **funct** when called from `nag_opt_simplex (e04ccc)`.

Note: **funct** should be tested separately before being used in conjunction with `nag_opt_simplex (e04ccc)`. The array **xc** must **not** be changed within **funct**.

3: **x[n]** – double *Input/Output*

On entry: a guess at the position of the minimum. Note that the problem should be scaled so that the values of the variables x_1, x_2, \dots, x_n are of order unity.

On exit: the value of x corresponding to the function value returned in **fmin**.

4: **fmin** – double * *Output*

On exit: the lowest function value found.

5: **options** – Nag_E04_Opt * *Input/Output*

On entry/exit: a pointer to a structure of type `Nag_E04_Opt` whose members are optional arguments for `nag_opt_simplex (e04ccc)`. These structure members offer the means of adjusting some of the

argument values of the algorithm and on output will supply further details of the results. A description of the members of **options** is given below in Section 10.2.

If any of these optional arguments are required then the structure **options** should be declared and initialized by a call to `nag_opt_init` (e04xxc) and supplied as an argument to `nag_opt_simplex` (e04ccc). However, if the optional arguments are not required the NAG defined null pointer, `E04_DEFAULT`, can be used in the function call.

6: **comm** – Nag_Comm * *Input/Output*

Note: **comm** is a NAG defined type (see Section 3.2.1.1 in the Essential Introduction).

On entry/exit: structure containing pointers for communication to user-supplied functions; see the above description of **funct** for details. If you do not need to make use of this communication feature the null pointer `NAGCOMM_NULL` may be used in the call to `nag_opt_simplex` (e04ccc); **comm** will then be declared internally for use in calls to user-supplied functions.

7: **fail** – NagError * *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

5.1 Description of Printed Output

Intermediate and final results are printed out by default. The level of printed output can be controlled with the option **options.print_level** (see Section 10.2). The default, **options.print_level** = `Nag_Soln_Iter` provides a single line of output at each iteration and the final result. The line of results printed at each iteration gives:

Itn	the current iteration number k .
Nfun	the cumulative number of calls made to funct .
Fmin	the smallest function value in the current simplex.
Fmax	the largest function value in the current simplex.

The printout of the final result consists of:

x	the final point x^* .
Function value	the value of $F(x^*)$.

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument **options.print_level** had an illegal value.

NE_INT_ARG_LT

On entry, **n** = $\langle value \rangle$.
Constraint: **n** ≥ 1 .

NE_INVALID_INT_RANGE_1

Value $\langle value \rangle$ given to **options.max_iter** is not valid. Correct range is **options.max_iter** > 0 .

NE_INVALID_REAL_RANGE_E

Value $\langle value \rangle$ given to **options.optim_tol** is not valid. Correct range is **options.optim_tol** $\geq \epsilon$.

NE_NOT_APPEND_FILE

Cannot open file $\langle string \rangle$ for appending.

NE_NOT_CLOSE_FILE

Cannot close file $\langle string \rangle$.

NE_OPT_NOT_INIT

Options structure not initialized.

NE_USER_STOP

User requested termination, user flag value = $\langle value \rangle$

This exit occurs if you set **comm** \rightarrow **flag** to a negative value in **funct**. If **fail** is supplied the value of **fail.errnum** will be the same as your setting of **comm** \rightarrow **flag**.

NW_TOO_MANY_ITER

The maximum number of iterations, $\langle value \rangle$, have been performed. **options.max_iter** evaluations of $F(x)$ have been completed, nag_opt_simplex (e04ccc) has been terminated prematurely. Check the coding of the function **funct** before increasing the value of **options.max_iter**.

7 Accuracy

On a successful exit the accuracy will be as defined by **options.optim_tol** (see Section 10.2).

8 Further Comments

The time taken depends on the number of variables, the behaviour of $F(x)$ and the distance of the starting point from the minimum. Each iteration consists of 1 or 2 evaluations of $F(x)$ unless the size of the simplex is reduced, in which case $n + 1$ evaluations are required.

9 Example

This example locates a minimum of the function:

$$F = e^{x_1} (4x_1^2 + 2x_2^2 + 4x_1x_2 + 2x_2 + 1).$$

The program uses $(-1.0, 1.0)$ as the initial guess at the position of the minimum.

The **options** structure is declared and initialized by nag_opt_init (e04xxc). One option is read from the data file by the use of nag_opt_read (e04xyc).

9.1 Program Text

```
/* nag_opt_simplex (e04ccc) Example Program.
 *
 * Copyright 1996 Numerical Algorithms Group.
 *
 * Mark 4, 1996.
 * Mark 6 revised, 2000.
 * Mark 7 revised, 2001.
 * Mark 7b revised, 2004.
 * Mark 8 revised, 2004.
 */

#include <math.h>
#include <stdio.h>
#include <string.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nage04.h>
```

```

#include <nagx02.h>
#include <nagx04.h>

#ifdef __cplusplus
extern "C" {
#endif
static void NAG_CALL funct(Integer n, double *xc, double *fc, Nag_Comm *comm);
#ifdef __cplusplus
}
#endif

int main(int argc, char *argv[])
{
    FILE          *fpout;
    char          *optionsfile = 0;
    char          *outfile = 0;
    Nag_Boolean   print;
    Integer       exit_status = 0, n;
    Nag_Comm     comm;
    Nag_E04_Opt  options;
    double        objf, *x = 0;
    NagError     fail;

    INIT_FAIL(fail);

    /* Check for command-line IO options */
    fpout = nag_example_file_io(argc, argv, "-results", NULL);
    (void) nag_example_file_io(argc, argv, "-options", &optionsfile);
    (void) nag_example_file_io(argc, argv, "-nag_write", &outfile);
    if (!outfile)
    {
        outfile = NAG_ALLOC(7, char);
        strcpy(outfile, "stdout");
    }

    fprintf(fpout, "nag_opt_simplex (e04ccc) Example Program Results\n");
    n = 2;
    if (n >= 1)
    {
        if (!(x = NAG_ALLOC(n, double)))
        {
            fprintf(fpout, "Allocation failure\n");
            exit_status = -1;
            goto END;
        }
    }
    else
    {
        fprintf(fpout, "Invalid n.\n");
        exit_status = 1;
        return exit_status;
    }
    /* nag_opt_init (e04xxc).
     * Initialization function for option setting
     */
    nag_opt_init(&options);
    strcpy(options.outfile, outfile);
    /* Read remaining option value from file */
    print = Nag_TRUE;
    /* nag_opt_read (e04xyc).
     * Read options from a text file
     */
    if (strcmp(outfile, "stdout"))
        fclose(fpout);
    nag_opt_read("e04ccc", optionsfile, &options, print, options.outfile, &fail);
    if (strcmp(outfile, "stdout"))
    {
        fpout = fopen(outfile, "a");
    }
    if (fail.code != NE_NOERROR)

```

```

    {
        fprintf(fpout, "Error from nag_opt_read (e04xyc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }

/* Starting values */
x[0] = -1.0;
x[1] = 1.0;

/* nag_opt_simplex (e04ccc), see above. */
if (strcmp(outfile, "stdout"))
    fclose(fpout);
nag_opt_simplex(n, funct, x, &objf, &options, &comm, &fail);
if (strcmp(outfile, "stdout"))
    {
        fpout = fopen(outfile, "a");
    }
if (fail.code != NE_NOERROR)
    {
        fprintf(fpout, "Error from nag_opt_simplex (e04ccc).\n%s\n",
                fail.message);
        exit_status = 1;
        goto END;
    }

END:
if (fpout != stdout) fclose(fpout);
if (x) NAG_FREE(x);
if (optionsfile) NAG_FREE(optionsfile);
if (outfile) NAG_FREE(outfile);

return exit_status;
}

static void NAG_CALL funct(Integer n, double *xc, double *objf, Nag_Comm *comm)
{
    *objf = exp(xc[0]) * (xc[0] * 4.0 * (xc[0] + xc[1]) +
                        xc[1] * 2.0 * (xc[1] + 1.0) + 1.0);
}

```

9.2 Program Data

nag_opt_simplex (e04ccc) Example Program Optional Parameters

Following optional parameter settings are read by e04xyc

```
begin e04ccc
```

```
/* Error tolerance */
```

```
optim_tol = 1.0e-14
end
```

9.3 Program Results

nag_opt_simplex (e04ccc) Example Program Results

Optional parameter setting for e04ccc.

```
-----
Option file: e04ccce.opt
```

```
optim_tol set to 1.00e-14
```

```
Parameters to e04ccc
```

```
-----
Number of variables..... 2
```

```

optim_tol..... 1.00e-14  max_iter..... 1500
print_level..... Nag_Soln_Iter  machine precision..... 1.11e-16
outfile..... stdout

```

Results from e04ccc:

Iteration results:

Itn	Nfun	Fmin	Fmax
1	8	1.6555e+00	2.1890e+00
2	10	1.6555e+00	1.8394e+00
3	12	1.6555e+00	1.7411e+00
4	14	1.6390e+00	1.7186e+00
5	16	1.3043e+00	1.6555e+00
6	18	6.5743e-01	1.6390e+00
7	20	1.1591e-02	1.3043e+00
8	22	1.1591e-02	7.1164e-01
9	24	1.1591e-02	6.5743e-01
10	25	1.1591e-02	4.1777e-01
11	27	1.1591e-02	2.6732e-01
12	29	1.1591e-02	1.7074e-01
13	31	1.1591e-02	1.1521e-01
14	32	1.1591e-02	3.4176e-02
15	34	5.7249e-03	1.7677e-02
16	36	7.3787e-04	1.1591e-02
17	38	7.3787e-04	5.7249e-03
18	40	7.3787e-04	3.2615e-03
19	42	7.3787e-04	1.6350e-03
20	44	2.0075e-04	7.7690e-04
21	46	1.4405e-04	7.3787e-04
22	48	1.4122e-04	2.0075e-04
23	50	7.0567e-06	1.4405e-04
24	52	7.0567e-06	1.4122e-04
25	54	7.0567e-06	4.3563e-05
26	56	7.0567e-06	1.7745e-05
27	58	3.9935e-06	7.1149e-06
28	60	5.2918e-07	7.0567e-06
29	62	5.2918e-07	3.9935e-06
30	63	5.2918e-07	1.9298e-06
31	65	3.5086e-07	1.0480e-06
32	67	1.4131e-07	5.2918e-07
33	69	4.0509e-08	3.5086e-07
34	71	4.0509e-08	1.4131e-07
35	73	3.1231e-08	9.2018e-08
36	75	1.7885e-08	4.0509e-08
37	77	6.6510e-09	3.1231e-08
38	79	1.7968e-09	1.7885e-08
39	81	1.7046e-09	6.6510e-09
40	83	6.6865e-10	1.7968e-09
41	85	4.2377e-10	1.7046e-09
42	87	2.9017e-10	6.6865e-10
43	89	1.3301e-10	4.2377e-10
44	91	1.3266e-11	2.9017e-10
45	93	1.3266e-11	1.3301e-10
46	95	1.3266e-11	5.2888e-11
47	97	1.2211e-11	3.0726e-11
48	99	5.8587e-12	1.3266e-11
49	101	4.9166e-13	1.2211e-11
50	103	4.9166e-13	5.8587e-12
51	105	4.9166e-13	3.1498e-12
52	107	4.9166e-13	1.0272e-12
53	109	1.6291e-13	6.4340e-13
54	111	3.9172e-14	4.9166e-13
55	113	3.9172e-14	1.6291e-13
56	115	9.1522e-15	1.2026e-13
57	117	9.1522e-15	3.9172e-14
58	119	2.9287e-15	1.8304e-14

Final solution:

```

Vector x
      5.0000e-01
     -1.0000e-00

Final Function value is  2.9287e-15

```

10 Optional Arguments

A number of optional input and output arguments to `nag_opt_simplex` (e04ccc) are available through the structure argument **options**, type `Nag_E04_Opt`. A argument may be selected by assigning an appropriate value to the relevant structure member; those arguments not selected will be assigned default values. If no use is to be made of any of the optional arguments you should use the NAG defined null pointer, `E04_DEFAULT`, in place of **options** when calling `nag_opt_simplex` (e04ccc); the default settings will then be used for all arguments.

Before assigning values to **options** directly the structure **must** be initialized by a call to the function `nag_opt_init` (e04xxc). Values may then be assigned to the structure members in the normal C manner.

Option settings may also be read from a text file using the function `nag_opt_read` (e04xyc) in which case initialization of the **options** structure will be performed automatically if not already done. Any subsequent direct assignment to the **options** structure must **not** be preceded by initialization.

If an assignment of a function pointer in the **options** structure is required, this must be done directly in the calling program, it cannot be assigned using `nag_opt_read` (e04xyc).

10.1 Optional Argument Checklist and Default Values

For easy reference, the following list shows the members of **options** which are valid for `nag_opt_simplex` (e04ccc) together with their default values where relevant. The number ϵ is a generic notation for *machine precision* (see `nag_machine_precision` (X02AJC)).

Boolean list	Nag_TRUE
Nag_PrintType print_level	Nag_Soln_Iter
char outfile[80]	stdout
void (*print_fun)()	NULL
Integer max_iter	1500
double optim_tol	ϵ
Integer iter	
Integer nf	

10.2 Description of the Optional Arguments

list – Nag_Boolean Default = Nag_TRUE

On entry: if **options.list** = Nag_TRUE the argument settings in the call to `nag_opt_simplex` (e04ccc) will be printed.

print_level – Nag_PrintType Default = Nag_Soln_Iter

On entry: the level of results printout produced by `nag_opt_simplex` (e04ccc). The following values are available:

Nag_NoPrint	No output.
Nag_Soln	The final solution only.
Nag_Iter	One line of output for each iteration.
Nag_Soln_Iter	The final solution and one line of output for each iteration.
Nag_Soln_Iter_Full	The final solution and detailed printout at each iteration.

Details of each level of results printout are described in Section 10.3.1.

Constraint: **options.print_level** = Nag_NoPrint, Nag_Soln, Nag_Iter, Nag_Soln_Iter or Nag_Soln_Iter_Full.

outfile – const char[80] Default = stdout

On entry: the name of the file to which results should be printed. If **options.outfile**[0] = '\0' then the stdout stream is used.

print_fun – pointer to function Default = NULL

On entry: printing function defined by you; the prototype of **options.print_fun** is

```
void (*print_fun)(const Nag_Search_State *st, Nag_Comm *comm);
```

See Section 10.3.1 below for further details.

max_iter – Integer Default = 1500

On entry: the maximum number of iterations allowed before termination.

Constraint: **options.max_iter** > 0.

optim_tol – double Default = ϵ

On entry: the accuracy in x to which the solution is required. If f_i , for $i = 1, 2, \dots, n + 1$, are the individual function values at the vertices of a simplex and f_m is the mean of these values, then termination will occur when

$$\sqrt{\frac{1}{n+1} \sum_{i=1}^{n+1} (f_i - f_m)^2} < \mathbf{options.optim_tol}.$$

Constraint: **options.optim_tol** $\geq \epsilon$.

iter – Integer i

On exit: the number of iterations which have been performed by nag_opt_simplex (e04ccc).

nf – Integer i

On exit: the number of times that **funct** has been called.

10.3 Description of Printed Output

The level of printed output can be controlled with the structure members **options.list** and **options.print_level** (see Section 10.2). If **options.list** = Nag_TRUE then the argument values to nag_opt_simplex (e04ccc) are listed, whereas the printout of results is governed by the value of **options.print_level**. The default of **options.print_level** = Nag_Soln_Iter provides a single line of output at each iteration and the final result. This section describes all of the possible levels of results printout available from nag_opt_simplex (e04ccc).

When **options.print_level** = Nag_Iter or Nag_Soln_Iter a single line of output is produced on completion of each iteration, this gives the following values:

Itn	the current iteration number k .
Nfun	the cumulative number of calls made to funct .
Fmin	the smallest function value in the current simplex.
Fmax	the largest function value in the current simplex.

When **options.print_level** = Nag_Soln_Iter_Full more detailed results are given at each iteration. Additional values output are:

x the current point $x^{(k)}$.
Simplex Vertices of the simplex with their corresponding vectors containing the positions of the current simplex.

If **options.print_level** = Nag_Soln, Nag_Soln_Iter or Nag_Soln_Iter_Full the final result is printed out. This consists of:

x the final point x^* .
Function value the value of $F(x^*)$.

If **options.print_level** = Nag_NoPrint, printout will be suppressed; you can then print the final solution when nag_opt_simplex (e04ccc) returns to the calling program.

10.3.1 Output of results via a user-defined printing function

You may also specify your own print function for output of iteration results and the final solution by use of the **options.print_fun** function pointer, which has prototype

```
void (*print_fun)(const Nag_Search_State *st, Nag_Comm *comm);
```

The rest of this section can be skipped if the default printing facilities provide the required functionality.

When a user-defined function is assigned to **options.print_fun** this will be called in preference to the internal print function of nag_opt_simplex (e04ccc). Calls to the user-defined function are again controlled by means of the **options.print_level** member. Information is provided through **st** and **comm**, the two structure arguments to **options.print_fun**. If **st** → **it_prt** = Nag_TRUE then the results from the last iteration of nag_opt_simplex (e04ccc) are in the following members of **st**:

n – Integer

The number of variables.

x – double *

Points to the **st** → **n** memory locations holding the current point $x^{(k)}$.

fmin – double

Holds the smallest function value in the current simplex.

fmax – double

Holds the largest function value in the current simplex.

simplex – double *

Points to the $(\mathbf{st} \rightarrow \mathbf{n} + 1) \times \mathbf{st} \rightarrow \mathbf{n}$ memory locations. If we regard this pointer as pointing to a notional two-dimensional array then its **st** → **n** + 1 rows contain the **st** → **n** position vectors of the vertices of the current simplex.

iter – Integer

k , the number of iterations performed by nag_opt_simplex (e04ccc).

nf – Integer

The cumulative number of calls made to **funct**.

The relevant members of the structure **comm** are:

it_prt – Nag_Boolean

Will be Nag_TRUE when the print function is called with the result of the current iteration.

sol_prt – Nag_Boolean

Will be Nag_TRUE when the print function is called with the final result.

user – double *
iuser – Integer *
p – Pointer

Pointers for communication of user information. If used they must be allocated memory either before entry to `nag_opt_simplex` (e04ccc) or during a call to **funct** or **options.print_fun**. The type Pointer will be `void *` with a C compiler that defines `void *` and `char *` otherwise.
