

NAG Library Function Document

nag_fft_multiple_qtr_cosine (c06hdc)

1 Purpose

nag_fft_multiple_qtr_cosine (c06hdc) computes the discrete quarter-wave Fourier cosine transforms of m sequences of real data values.

2 Specification

```
#include <nag.h>
#include <nagc06.h>
```

```
void nag_fft_multiple_qtr_cosine (Nag_TransformDirection direct, Integer m,
    Integer n, double x[], const double trig[], NagError *fail)
```

3 Description

Given m sequences of n real data values x_j^p , for $j = 0, 1, \dots, n - 1$ and $p = 1, 2, \dots, m$, this function simultaneously calculates the quarter-wave Fourier cosine transforms of all the sequences defined by

$$\hat{x}_k^p = \frac{1}{\sqrt{n}} \left\{ \frac{1}{2} x_0^p + \sum_{j=1}^{n-1} x_j^p \cos \left(j(2k-1) \frac{\pi}{2n} \right) \right\} \quad \text{if } \mathbf{direct},$$

or its inverse

$$x_k^p = \frac{2}{\sqrt{n}} \sum_{j=0}^{n-1} \hat{x}_j^p \cos \left((2j-1) k \frac{\pi}{2n} \right) \quad \text{if } \mathbf{direct},$$

for $k = 0, 1, \dots, n - 1$ and $p = 1, 2, \dots, m$.

(Note the scale factor $\frac{1}{\sqrt{n}}$ in this definition.)

A call of the function with **direct** = Nag_ForwardTransform followed by a call with **direct** = Nag_BackwardTransform will restore the original data (but see Section 8).

The transform calculated by this function can be used to solve Poisson's equation when the derivative of the solution is specified at the left boundary, and the solution is specified at the right boundary (Swarztrauber (1977)).

The function uses a variant of the fast Fourier transform (FFT) algorithm (Brigham (1974)) known as the Stockham self-sorting algorithm, described in Temperton (1983), together with pre- and post-processing stages described in Swarztrauber (1982). Special coding is provided for the factors 2, 3, 4, 5 and 6.

4 References

Brigham E O (1974) *The Fast Fourier Transform* Prentice–Hall

Swarztrauber P N (1977) The methods of cyclic reduction, Fourier analysis and the FACR algorithm for the discrete solution of Poisson's equation on a rectangle *SIAM Rev.* **19** (3) 490–501

Swarztrauber P N (1982) Vectorizing the FFT's *Parallel Computation* (ed G Rodrigue) 51–83 Academic Press

Temperton C (1983) Fast mixed-radix real Fourier transforms *J. Comput. Phys.* **52** 340–350

5 Arguments

- 1: **direct** – Nag_TransformDirection *Input*
On entry: if the forward transform as defined in Section 3 is to be computed, then **direct** must be set equal to Nag_ForwardTransform. If the backward transform is to be computed, that is the inverse, then **direct** must be set equal to Nag_BackwardTransform.
Constraint: **direct** = Nag_ForwardTransform or Nag_BackwardTransform.
- 2: **m** – Integer *Input*
On entry: the number of sequences to be transformed, m .
Constraint: $m \geq 1$.
- 3: **n** – Integer *Input*
On entry: the number of real values in each sequence, n .
Constraint: $n \geq 1$.
- 4: **x**[$m \times n$] – double *Input/Output*
On entry: the m data sequences stored in **x** consecutively. If the data values of the p th sequence to be transformed are denoted by x_j^p , for $j = 0, 1, \dots, n - 1$ and $p = 1, 2, \dots, m$, then the first mn elements of the array **x** must contain the values
$$x_0^1, x_1^1, \dots, x_{n-1}^1, \quad x_0^2, x_1^2, \dots, x_{n-1}^2, \quad \dots, \quad x_0^m, x_1^m, \dots, x_{n-1}^m,$$
On exit: the m quarter-wave cosine transforms stored consecutively overwriting the corresponding original sequence.
- 5: **trig**[$2 \times n$] – const double *Input*
On entry: trigonometric coefficients as returned by a call of nag_fft_init_trig (c06gzc). nag_fft_multiple_qtr_cosine (c06hdc) makes a simple check to ensure that **trig** has been initialized and that the initialization is compatible with the value of **n**.
- 6: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument **direct** had an illegal value.

NE_C06_NOT_TRIG

Value of **n** and **trig** array are incompatible or **trig** array not initialized.

NE_INT_ARG_LT

On entry, **m** = $\langle value \rangle$.

Constraint: $m \geq 1$.

On entry, **n** = $\langle value \rangle$.

Constraint: $n \geq 1$.

7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

8 Further Comments

The time taken is approximately proportional to $nm \log n$, but also depends on the factors of n . The function is fastest if the only prime factors of n are 2, 3 and 5, and is particularly slow if n is a large prime, or has large prime factors.

9 Example

This program reads in sequences of real data values and prints their quarter-wave cosine transforms as computed by `nag_fft_multiple_qtr_cosine (c06hdc)` with `direct = Nag_ForwardTransform`. It then calls `nag_fft_multiple_qtr_cosine (c06hdc)` again with `direct = Nag_BackwardTransform` and prints the results which may be compared with the original data.

9.1 Program Text

```

/* nag_fft_multiple_qtr_cosine (c06hdc) Example Program.
 *
 * Copyright 1991 Numerical Algorithms Group.
 *
 * Mark 2, 1991.
 * Mark 8 revised, 2004.
 */

#include <nag.h>
#include <nagx04.h>
#include <stdio.h>
#include <nag_stdlib.h>
#include <nagc06.h>

#define X(I, J) x[(I) *n + (J)]

int main(int argc, char *argv[])
{
    FILE      *fpin, *fpout;
    Integer   exit_status = 0, i, j, m, n;
    NagError  fail;
    double    *trig = 0, *x = 0;

    INIT_FAIL(fail);

    /* Check for command-line IO options */
    fpin = nag_example_file_io(argc, argv, "-data", NULL);
    fpout = nag_example_file_io(argc, argv, "-results", NULL);
    fprintf(fpout,
            "nag_fft_multiple_qtr_cosine (c06hdc) Example Program Results\n");
    fscanf(fpin, "%*[^\\n]"); /* Skip heading in data file */
    while (fscanf(fpin, "%ld %ld", &m, &n) != EOF)
    {
        if (m >= 1 && n >= 1)
        {
            if (!(trig = NAG_ALLOC(2*n, double)) ||
                !(x = NAG_ALLOC(m*n, double)))
            {
                fprintf(fpout, "Allocation failure\n");
                exit_status = -1;
                goto END;
            }
        }
        else
        {
            fprintf(fpout, "Invalid m or n.\n");
        }
    }
}

```

```

        exit_status = 1;
        return exit_status;
    }
    fscanf(fpin, "%*[\n]"); /* Skip text in data file */
    fscanf(fpin, "%*[\n]");
    for (i = 0; i < m; ++i)
        for (j = 0; j < n; ++j)
            fscanf(fpin, "%lf", &X(i, j));
    fprintf(fpout, "\nOriginal data values\n\n");
    for (i = 0; i < m; ++i)
    {
        for (j = 0; j < n; ++j)
            fprintf(fpout, " %10.4f%s", X(i, j),
                    (j%7 == 6 && j != n-1?"\n":""));
        fprintf(fpout, "\n");
    }
    /* Initialise trig array */
    /* nag_fft_init_trig (c06gzc).
    * Initialization function for other c06 functions
    */
    nag_fft_init_trig(n, trig, &fail);
    if (fail.code != NE_NOERROR)
    {
        fprintf(fpout, "Error from nag_fft_init_trig (c06gzc).\n%s\n",
                fail.message);
        exit_status = 1;
        goto END;
    }

    /* Compute transform */
    /* nag_fft_multiple_qtr_cosine (c06hdc).
    * Discrete quarter-wave cosine transform
    */
    nag_fft_multiple_qtr_cosine(Nag_ForwardTransform, m, n, x, trig, &fail);
    if (fail.code != NE_NOERROR)
    {
        fprintf(fpout,
                "Error from nag_fft_multiple_qtr_cosine (c06hdc).\n%s\n",
                fail.message);
        exit_status = 1;
        goto END;
    }

    fprintf(fpout, "\nDiscrete quarter-wave Fourier cosine transforms\n\n");
    for (i = 0; i < m; ++i)
    {
        for (j = 0; j < n; ++j)
            fprintf(fpout, " %10.4f%s", X(i, j),
                    (j%7 == 6 && j != n-1?"\n":""));
        fprintf(fpout, "\n");
    }
    /* Compute inverse transform */
    /* nag_fft_multiple_qtr_cosine (c06hdc), see above. */
    nag_fft_multiple_qtr_cosine(Nag_BackwardTransform, m, n, x, trig, &fail);
    if (fail.code != NE_NOERROR)
    {
        fprintf(fpout,
                "Error from nag_fft_multiple_qtr_cosine (c06hdc).\n%s\n",
                fail.message);
        exit_status = 1;
        goto END;
    }

    fprintf(fpout, "\nOriginal data as restored by inverse transform\n\n");
    for (i = 0; i < m; ++i)
    {
        for (j = 0; j < n; ++j)
            fprintf(fpout, " %10.4f%s", X(i, j),
                    (j%7 == 6 && j != n-1?"\n":""));
        fprintf(fpout, "\n");
    }

```

```

    }

END:
    if (trig) NAG_FREE(trig);
    if (x) NAG_FREE(x);
}

if (fpin != stdin) fclose(fpin);
if (fpout != stdout) fclose(fpout);
return exit_status;
}

```

9.2 Program Data

nag_fft_multiple_qtr_cosine (c06hdc) Example Program Data
 3 6 : Number of sequences, m, and number of values in each sequence, n
 Real data sequences

0.3854	0.6772	0.1138	0.6751	0.6362	0.1424
0.5417	0.2983	0.1181	0.7255	0.8638	0.8723
0.9172	0.0644	0.6037	0.6430	0.0428	0.4815

9.3 Program Results

nag_fft_multiple_qtr_cosine (c06hdc) Example Program Results

Original data values

0.3854	0.6772	0.1138	0.6751	0.6362	0.1424
0.5417	0.2983	0.1181	0.7255	0.8638	0.8723
0.9172	0.0644	0.6037	0.6430	0.0428	0.4815

Discrete quarter-wave Fourier cosine transforms

0.7257	-0.2216	0.1011	0.2355	-0.1406	-0.2282
0.7479	-0.6172	0.4112	0.0791	0.1331	-0.0906
0.6713	-0.1363	-0.0064	-0.0285	0.4758	0.1475

Original data as restored by inverse transform

0.3854	0.6772	0.1138	0.6751	0.6362	0.1424
0.5417	0.2983	0.1181	0.7255	0.8638	0.8723
0.9172	0.0644	0.6037	0.6430	0.0428	0.4815
