

## NAG Library Routine Document

### F07QRF (ZSPTRF)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

#### 1 Purpose

F07QRF (ZSPTRF) computes the Bunch–Kaufman factorization of a complex symmetric matrix, using packed storage.

#### 2 Specification

SUBROUTINE F07QRF (UPLO, N, AP, IPIV, INFO)

INTEGER N, IPIV(N), INFO  
 COMPLEX (KIND=nag\_wp) AP(\*)  
 CHARACTER(1) UPLO

The routine may be called by its LAPACK name *zsptf*.

#### 3 Description

F07QRF (ZSPTRF) factorizes a complex symmetric matrix  $A$ , using the Bunch–Kaufman diagonal pivoting method and packed storage.  $A$  is factorized as either  $A = PUDU^T P^T$  if UPLO = 'U' or  $A = PLDL^T P^T$  if UPLO = 'L', where  $P$  is a permutation matrix,  $U$  (or  $L$ ) is a unit upper (or lower) triangular matrix and  $D$  is a symmetric block diagonal matrix with 1 by 1 and 2 by 2 diagonal blocks;  $U$  (or  $L$ ) has 2 by 2 unit diagonal blocks corresponding to the 2 by 2 blocks of  $D$ . Row and column interchanges are performed to ensure numerical stability while preserving symmetry.

#### 4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

#### 5 Parameters

1: UPLO – CHARACTER(1) *Input*

*On entry:* specifies whether the upper or lower triangular part of  $A$  is stored and how  $A$  is to be factorized.

UPLO = 'U'

The upper triangular part of  $A$  is stored and  $A$  is factorized as  $PUDU^T P^T$ , where  $U$  is upper triangular.

UPLO = 'L'

The lower triangular part of  $A$  is stored and  $A$  is factorized as  $PLDL^T P^T$ , where  $L$  is lower triangular.

*Constraint:* UPLO = 'U' or 'L'.

2: N – INTEGER *Input*

*On entry:*  $n$ , the order of the matrix  $A$ .

*Constraint:*  $N \geq 0$ .

3: AP(\*) – COMPLEX (KIND=nag\_wp) array Input/Output

**Note:** the dimension of the array AP must be at least  $\max(1, N \times (N + 1)/2)$ .

*On entry:* the  $n$  by  $n$  symmetric matrix  $A$ , packed by columns.

More precisely,

if UPLO = 'U', the upper triangle of  $A$  must be stored with element  $A_{ij}$  in  $AP(i + j(j - 1)/2)$  for  $i \leq j$ ;

if UPLO = 'L', the lower triangle of  $A$  must be stored with element  $A_{ij}$  in  $AP(i + (2n - j)(j - 1)/2)$  for  $i \geq j$ .

*On exit:*  $A$  is overwritten by details of the block diagonal matrix  $D$  and the multipliers used to obtain the factor  $U$  or  $L$  as specified by UPLO.

4: IPIV(N) – INTEGER array Output

*On exit:* details of the interchanges and the block structure of  $D$ . More precisely,

if  $IPIV(i) = k > 0$ ,  $d_{ii}$  is a 1 by 1 pivot block and the  $i$ th row and column of  $A$  were interchanged with the  $k$ th row and column;

if UPLO = 'U' and  $IPIV(i - 1) = IPIV(i) = -l < 0$ ,  $\begin{pmatrix} d_{i-1,i-1} & \bar{d}_{i,i-1} \\ \bar{d}_{i,i-1} & d_{ii} \end{pmatrix}$  is a 2 by 2 pivot block and the  $(i - 1)$ th row and column of  $A$  were interchanged with the  $l$ th row and column;

if UPLO = 'L' and  $IPIV(i) = IPIV(i + 1) = -m < 0$ ,  $\begin{pmatrix} d_{ii} & d_{i+1,i} \\ d_{i+1,i} & d_{i+1,i+1} \end{pmatrix}$  is a 2 by 2 pivot block and the  $(i + 1)$ th row and column of  $A$  were interchanged with the  $m$ th row and column.

5: INFO – INTEGER Output

*On exit:* INFO = 0 unless the routine detects an error (see Section 6).

## 6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO =  $-i$ , the  $i$ th parameter had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

If INFO =  $i$ ,  $d(i, i)$  is exactly zero. The factorization has been completed, but the block diagonal matrix  $D$  is exactly singular, and division by zero will occur if it is used to solve a system of equations.

## 7 Accuracy

If UPLO = 'U', the computed factors  $U$  and  $D$  are the exact factors of a perturbed matrix  $A + E$ , where

$$|E| \leq c(n)\epsilon P|U||D||U^T|P^T,$$

$c(n)$  is a modest linear function of  $n$ , and  $\epsilon$  is the *machine precision*.

If UPLO = 'L', a similar statement holds for the computed factors  $L$  and  $D$ .

## 8 Further Comments

The elements of  $D$  overwrite the corresponding elements of  $A$ ; if  $D$  has 2 by 2 blocks, only the upper or lower triangle is stored, as specified by UPLO.

The unit diagonal elements of  $U$  or  $L$  and the 2 by 2 unit diagonal blocks are not stored. The remaining elements of  $U$  or  $L$  overwrite elements in the corresponding columns of  $A$ , but additional row interchanges must be applied to recover  $U$  or  $L$  explicitly (this is seldom necessary). If  $\text{IPIV}(i) = i$ , for  $i = 1, 2, \dots, n$ , then  $U$  or  $L$  are stored explicitly in packed form (except for their unit diagonal elements which are equal to 1).

The total number of real floating point operations is approximately  $\frac{4}{3}n^3$ .

A call to F07QRF (ZSPTRF) may be followed by calls to the routines:

F07QSF (ZSPTRS) to solve  $AX = B$ ;

F07QUF (ZSPCON) to estimate the condition number of  $A$ ;

F07QWF (ZSPTRI) to compute the inverse of  $A$ .

The real analogue of this routine is F07PDF (DSPTRF).

## 9 Example

This example computes the Bunch–Kaufman factorization of the matrix  $A$ , where

$$A = \begin{pmatrix} -0.39 - 0.71i & 5.14 - 0.64i & -7.86 - 2.96i & 3.80 + 0.92i \\ 5.14 - 0.64i & 8.86 + 1.81i & -3.52 + 0.58i & 5.32 - 1.59i \\ -7.86 - 2.96i & -3.52 + 0.58i & -2.83 - 0.03i & -1.54 - 2.86i \\ 3.80 + 0.92i & 5.32 - 1.59i & -1.54 - 2.86i & -0.56 + 0.12i \end{pmatrix},$$

using packed storage.

### 9.1 Program Text

```

Program f07qrfe

!      F07QRF Example Program Text
!
!      Mark 24 Release. NAG Copyright 2012.
!
!      .. Use Statements ..
      Use nag_library, Only: nag_wp, x04ddf, zsptrf
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Integer                     :: i, ifail, info, j, n
      Character (1)               :: uplo
!      .. Local Arrays ..
      Complex (Kind=nag_wp), Allocatable :: ap(:)
      Integer, Allocatable        :: ipiv(:)
      Character (1)               :: clabs(1), rlabs(1)
!      .. Executable Statements ..
      Write (nout,*) 'F07QRF Example Program Results'
!      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n

      Allocate (ap(n*(n+1)/2),ipiv(n))

!      Read A from data file

      Read (nin,*) uplo
      If (uplo=='U') Then
         Read (nin,*)((ap(i+j*(j-1)/2),j=i,n),i=1,n)

```

```

      Else If (uplo=='L') Then
        Read (nin,*)((ap(i+(2*n-j)*(j-1)/2),j=1,i),i=1,n)
      End If

!      Factorize A
!      The NAG name equivalent of zsptrf is f07qrf
      Call zsptrf(uplo,n,ap,ipiv,info)

      Write (nout,*)
      Flush (nout)

!      Print details of factorization

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
      Call x04ddf(uplo,'Nonunit',n,ap,'Bracketed','F7.4', &
        'Details of factorization','Integer',rlabs,'Integer',clabs,80,0,ifail)

!      Print pivot indices

      Write (nout,*)
      Write (nout,*) 'IPIV'
      Write (nout,99999) ipiv(1:n)

      If (info/=0) Write (nout,*) 'The factor D is singular'

99999 Format ((1X,I12,3I18))
      End Program f07qrfe

```

## 9.2 Program Data

F07QRF Example Program Data

```

  4                                     :Value of N
  'L'                                   :Value of UPLO
(-0.39,-0.71)
( 5.14,-0.64) ( 8.86, 1.81)
(-7.86,-2.96) (-3.52, 0.58) (-2.83,-0.03)
( 3.80, 0.92) ( 5.32,-1.59) (-1.54,-2.86) (-0.56, 0.12) :End of matrix A

```

## 9.3 Program Results

F07QRF Example Program Results

Details of factorization

	1	2	3	4
1	(-0.3900,-0.7100)			
2	(-7.8600,-2.9600)	(-2.8300,-0.0300)		
3	( 0.5279,-0.3715)	(-0.6078, 0.2811)	( 4.4079, 5.3991)	
4	( 0.4426, 0.1936)	(-0.4823, 0.0150)	(-0.1071,-0.3157)	(-2.0954,-2.2011)

IPIV

-3	-3	3	4
----	----	---	---

---