# NAG Library Routine Document F07PBF (DSPSVX)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

# 1 Purpose

F07PBF (DSPSVX) uses the diagonal pivoting factorization

$$A = UDU^{\mathsf{T}}$$
 or  $A = LDL^{\mathsf{T}}$ 

to compute the solution to a real system of linear equations

$$AX = B$$

where A is an n by n symmetric matrix stored in packed format and X and B are n by r matrices. Error bounds on the solution and a condition estimate are also provided.

# 2 Specification

```
SUBROUTINE F07PBF (FACT, UPLO, N, NRHS, AP, AFP, IPIV, B, LDB, X, LDX, RCOND, FERR, BERR, WORK, IWORK, INFO)

INTEGER N, NRHS, IPIV(N), LDB, LDX, IWORK(N), INFO

REAL (KIND=nag_wp) AP(*), AFP(*), B(LDB,*), X(LDX,*), RCOND, FERR(NRHS), BERR(NRHS), WORK(3*N)

CHARACTER(1) FACT, UPLO
```

The routine may be called by its LAPACK name dspsvx.

## 3 Description

F07PBF (DSPSVX) performs the following steps:

- 1. If FACT = 'N', the diagonal pivoting method is used to factor A as  $A = UDU^{T}$  if UPLO = 'U' or  $A = LDL^{T}$  if UPLO = 'L', where U (or L) is a product of permutation and unit upper (lower) triangular matrices and D is symmetric and block diagonal with 1 by 1 and 2 by 2 diagonal blocks.
- 2. If some  $d_{ii} = 0$ , so that D is exactly singular, then the routine returns with INFO = i. Otherwise, the factored form of A is used to estimate the condition number of the matrix A. If the reciprocal of the condition number is less than **machine precision**, INFO = N + 1 is returned as a warning, but the routine still goes on to solve for X and compute error bounds as described below.
- 3. The system of equations is solved for X using the factored form of A.
- 4. Iterative refinement is applied to improve the computed solution matrix and to calculate error bounds and backward error estimates for it.

#### 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia http://www.netlib.org/lapack/lug

Golub G H and Van Loan C F (1996) Matrix Computations (3rd Edition) Johns Hopkins University Press, Baltimore

Higham N J (2002) Accuracy and Stability of Numerical Algorithms (2nd Edition) SIAM, Philadelphia

Mark 25 F07PBF.1

F07PBF NAG Library Manual

#### 5 Parameters

#### 1: FACT - CHARACTER(1)

Input

On entry: specifies whether or not the factorized form of the matrix A has been supplied.

FACT = 'F'

AFP and IPIV contain the factorized form of the matrix A. AFP and IPIV will not be modified.

FACT = 'N'

The matrix A will be copied to AFP and factorized.

Constraint: FACT = 'F' or 'N'.

#### 2: UPLO - CHARACTER(1)

Input

On entry: if UPLO = 'U', the upper triangle of A is stored.

If UPLO = 'L', the lower triangle of A is stored.

*Constraint*: UPLO = 'U' or 'L'.

#### 3: N – INTEGER

Input

On entry: n, the number of linear equations, i.e., the order of the matrix A.

Constraint: N > 0.

#### 4: NRHS – INTEGER

Input

On entry: r, the number of right-hand sides, i.e., the number of columns of the matrix B.

Constraint: NRHS  $\geq 0$ .

#### 5: AP(\*) - REAL (KIND=nag wp) array

Input

**Note**: the dimension of the array AP must be at least  $max(1, N \times (N+1)/2)$ .

On entry: the n by n symmetric matrix A, packed by columns.

More precisely,

if UPLO = 'U', the upper triangle of A must be stored with element  $A_{ij}$  in AP(i+j(j-1)/2) for  $i \leq j$ ;

if UPLO = 'L', the lower triangle of A must be stored with element  $A_{ij}$  in AP(i + (2n - j)(j - 1)/2) for  $i \ge j$ .

# 6: AFP(\*) - REAL (KIND=nag\_wp) array

Input/Output

**Note**: the dimension of the array AFP must be at least  $max(1, N \times (N+1)/2)$ .

On entry: if FACT = 'F', AFP contains the block diagonal matrix D and the multipliers used to obtain the factor U or L from the factorization  $A = UDU^{T}$  or  $A = LDL^{T}$  as computed by F07PDF (DSPTRF), stored as a packed triangular matrix in the same storage format as A.

On exit: if FACT = 'N', AFP contains the block diagonal matrix D and the multipliers used to obtain the factor U or L from the factorization  $A = UDU^T$  or  $A = LDL^T$  as computed by F07PDF (DSPTRF), stored as a packed triangular matrix in the same storage format as A.

## 7: IPIV(N) - INTEGER array

Input/Output

On entry: if FACT = 'F', IPIV contains details of the interchanges and the block structure of D, as determined by F07PDF (DSPTRF).

F07PBF.2 Mark 25

F07PBF

if IPIV(i) = k > 0,  $d_{ii}$  is a 1 by 1 pivot block and the *i*th row and column of A were interchanged with the kth row and column;

$$\text{if UPLO} = \text{'U'} \text{ and } \text{IPIV}(i-1) = \text{IPIV}(i) = -l < 0, \\ \begin{pmatrix} d_{\underline{i}-1,i-1} & \bar{d}_{i,i-1} \\ \bar{d}_{i,i-1} & d_{ii} \end{pmatrix} \text{ is a 2 by 2 pivot}$$

block and the (i-1)th row and column of A were interchanged with the lth row and column:

if UPLO = 'L' and IPIV
$$(i) = \text{IPIV}(i+1) = -m < 0$$
,  $\begin{pmatrix} d_{ii} & d_{i+1,i} \\ d_{i+1,i} & d_{i+1,i+1} \end{pmatrix}$  is a 2 by 2 pivot

block and the (i+1)th row and column of A were interchanged with the mth row and column.

On exit: if FACT = 'N', IPIV contains details of the interchanges and the block structure of D, as determined by F07PDF (DSPTRF), as described above.

#### 8: B(LDB,\*) - REAL (KIND=nag wp) array

Input

**Note**: the second dimension of the array B must be at least max(1, NRHS).

On entry: the n by r right-hand side matrix B.

#### 9: LDB – INTEGER

Input

On entry: the first dimension of the array B as declared in the (sub)program from which F07PBF (DSPSVX) is called.

Constraint: LDB  $\geq \max(1, N)$ .

## 10: X(LDX, \*) - REAL (KIND=nag wp) array

Output

**Note**: the second dimension of the array X must be at least max(1, NRHS).

On exit: if INFO = 0 or N + 1, the n by r solution matrix X.

#### 11: LDX – INTEGER

Input

On entry: the first dimension of the array X as declared in the (sub)program from which F07PBF (DSPSVX) is called.

Constraint: LDX  $\geq \max(1, N)$ .

## 12: RCOND - REAL (KIND=nag\_wp)

Output

On exit: the estimate of the reciprocal condition number of the matrix A. If RCOND = 0.0, the matrix may be exactly singular. This condition is indicated by INFO > 0 and INFO  $\leq$  N. Otherwise, if RCOND is less than the **machine precision**, the matrix is singular to working precision. This condition is indicated by INFO = N + 1.

### 13: FERR(NRHS) – REAL (KIND=nag wp) array

Output

On exit: if INFO = 0 or N + 1, an estimate of the forward error bound for each computed solution vector, such that  $\|\hat{x}_j - x_j\|_{\infty} / \|x_j\|_{\infty} \le \text{FERR}(j)$  where  $\hat{x}_j$  is the *j*th column of the computed solution returned in the array X and  $x_j$  is the corresponding column of the exact solution X. The estimate is as reliable as the estimate for RCOND, and is almost always a slight overestimate of the true error.

## 14: BERR(NRHS) - REAL (KIND=nag\_wp) array

Output

On exit: if INFO = 0 or N + 1, an estimate of the component-wise relative backward error of each computed solution vector  $\hat{x}_j$  (i.e., the smallest relative change in any element of A or B that makes  $\hat{x}_j$  an exact solution).

15: WORK $(3 \times N)$  – REAL (KIND=nag wp) array

Workspace

Mark 25 F07PBF.3

F07PBF NAG Library Manual

16: IWORK(N) – INTEGER array

Workspace

17: INFO – INTEGER Output

On exit: INFO = 0 unless the routine detects an error (see Section 6).

# 6 Error Indicators and Warnings

INFO < 0

If INFO = -i, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0 and INFO < N

Element  $\langle value \rangle$  of the diagonal is exactly zero. The factorization has been completed, but the factor D is exactly singular, so the solution and error bounds could not be computed. RCOND = 0.0 is returned.

INFO = N + 1

D is nonsingular, but RCOND is less than *machine precision*, meaning that the matrix is singular to working precision. Nevertheless, the solution and error bounds are computed because there are a number of situations where the computed solution can be more accurate than the value of RCOND would suggest.

## 7 Accuracy

For each right-hand side vector b, the computed solution  $\hat{x}$  is the exact solution of a perturbed system of equations  $(A+E)\hat{x}=b$ , where

$$||E||_1 = O(\epsilon)||A||_1$$

where  $\epsilon$  is the *machine precision*. See Chapter 11 of Higham (2002) for further details.

If  $\hat{x}$  is the true solution, then the computed solution x satisfies a forward error bound of the form

$$\frac{\|x - \hat{x}\|_{\infty}}{\|\hat{x}\|_{\infty}} \le w_c \operatorname{cond}(A, \hat{x}, b)$$

where  $\operatorname{cond}(A, \hat{x}, b) = \||A^{-1}|(|A||\hat{x}| + |b|)\|_{\infty}/\|\hat{x}\|_{\infty} \leq \operatorname{cond}(A) = \||A^{-1}||A|\|_{\infty} \leq \kappa_{\infty}(A)$ . If  $\hat{x}$  is the jth column of X, then  $w_c$  is returned in BERR(j) and a bound on  $\|x - \hat{x}\|_{\infty}/\|\hat{x}\|_{\infty}$  is returned in FERR(j). See Section 4.4 of Anderson et al. (1999) for further details.

# 8 Parallelism and Performance

F07PBF (DSPSVX) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07PBF (DSPSVX) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

# **9** Further Comments

The factorization of A requires approximately  $\frac{1}{3}n^3$  floating-point operations.

F07PBF.4 Mark 25

For each right-hand side, computation of the backward error involves a minimum of  $4n^2$  floating-point operations. Each step of iterative refinement involves an additional  $6n^2$  operations. At most five steps of iterative refinement are performed, but usually only one or two steps are required. Estimating the forward error involves solving a number of systems of equations of the form Ax = b; the number is usually 4 or 5 and never more than 11. Each solution involves approximately  $2n^2$  operations.

The complex analogues of this routine are F07PPF (ZHPSVX) for Hermitian matrices, and F07QPF (ZSPSVX) for symmetric matrices.

## 10 Example

This example solves the equations

$$AX = B$$
,

where A is the symmetric matrix

$$A = \begin{pmatrix} -1.81 & 2.06 & 0.63 & -1.15 \\ 2.06 & 1.15 & 1.87 & 4.20 \\ 0.63 & 1.87 & -0.21 & 3.87 \\ -1.15 & 4.20 & 3.87 & 2.07 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 0.96 & 3.93 \\ 6.07 & 19.25 \\ 8.38 & 9.90 \\ 9.50 & 27.85 \end{pmatrix}$$

Error estimates for the solutions, and an estimate of the reciprocal of the condition number of the matrix A are also output.

## 10.1 Program Text

```
Program f07pbfe
      FO7PBF Example Program Text
!
!
      Mark 25 Release. NAG Copyright 2014.
!
      .. Use Statements ..
      Use nag_library, Only: dspsvx, nag_wp, x04caf
      .. Implicit None Statement ..
!
      Implicit None
1
      .. Parameters .
      Integer, Parameter
                                          :: nin = 5, nout = 6
                                          :: uplo = 'U'
      Character (1), Parameter
      .. Local Scalars ..
      Real (Kind=nag_wp)
                                          :: rcond
      Integer
                                          :: i, ifail, info, j, ldb, ldx, n, nrhs
!
      .. Local Arrays ..
      \label{eq:Real_condition} \textit{Real (Kind=nag\_wp), Allocatable} \quad :: \quad \textit{afp(:), ap(:), b(:,:), berr(:),}
                                          ferr(:), work(:), x(:,:)
:: ipiv(:), iwork(:)
      Integer, Allocatable
      .. Executable Statements ..
      Write (nout,*) 'F07PBF Example Program Results'
      Write (nout,*)
      Flush (nout)
      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n, nrhs
      ldb = n
      ldx = n
      Allocate (afp((n*(n+1))/2),ap((n*(n+1))/2),b(ldb,nrhs),berr(nrhs),ferr( &
        nrhs),work(3*n),x(ldx,nrhs),ipiv(n),iwork(n))
      Read the upper or lower triangular part of the matrix A from
      data file
      If (uplo=='U') Then
        Read (nin,*)((ap(i+(j*(j-1))/2),j=i,n),i=1,n)
      Else If (uplo=='L') Then
        Read (nin,*)((ap(i+((2*n-j)*(j-1))/2),j=1,i),i=1,n)
      End If
```

Mark 25 F07PBF.5

F07PBF NAG Library Manual

```
!
     Read B from data file
      Read (nin,*)(b(i,1:nrhs),i=1,n)
     Solve the equations AX = B for X
     The NAG name equivalent of dspsvx is f07pbf
      Call dspsvx('Not factored',uplo,n,nrhs,ap,afp,ipiv,b,ldb,x,ldx,rcond, &
        ferr,berr,work,iwork,info)
      If ((info==0) .Or. (info==n+1)) Then
1
        Print solution, error bounds and condition number
        ifail: behaviour on error exit
               =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
        ifail = 0
        Call x04caf('General',' ',n,nrhs,x,ldx,'Solution(s)',ifail)
        Write (nout,*)
        Write (nout,*) 'Backward errors (machine-dependent)'
        Write (nout, 99999) berr(1:nrhs)
        Write (nout,*)
        Write (nout,*) 'Estimated forward error bounds (machine-dependent)'
        Write (nout,99999) ferr(1:nrhs)
        Write (nout,*)
        Write (nout,*) 'Estimate of reciprocal condition number'
        Write (nout, 99999) rcond
       Write (nout,*)
        If (info==n+1) Then
         Write (nout,*)
         Write (nout,*) 'The matrix A is singular to working precision'
        End If
        Write (nout,99998) 'The diagonal block ', info, ' of D is zero'
     End If
99999 Format ((3X,1P,7E11.1))
99998 Format (1X,A,I3,A)
   End Program f07pbfe
```

#### 10.2 Program Data

```
FO7PBF Example Program Data
                           :Values of N and NRHS
 4
        2
 -1.81
        2.06
               0.63 -1.15
                     4.20
        1.15
              1.87
              -0.21 3.87
                      2.07 :End of matrix A
 0.96
        3.93
 6.07
       19.25
        9.90
 8.38
 9.50 27.85
                           :End of matrix B
```

#### 10.3 Program Results

```
FO7PBF Example Program Results
Solution(s)
      -5.0000
                  2.0000
1
2
      -2.0000
                  3.0000
3
       1.0000
                  4.0000
                  1.0000
       4.0000
Backward errors (machine-dependent)
      1.4E-16
                 1.0E-16
Estimated forward error bounds (machine-dependent)
```

F07PBF.6 Mark 25

2.5E-14 3.2E-14

Estimate of reciprocal condition number 1.3E-02

Mark 25 F07PBF.7 (last)