NAG Library Routine Document

F07GHF (DPPRFS)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F07GHF (DPPRFS) returns error bounds for the solution of a real symmetric positive definite system of linear equations with multiple right-hand sides, AX = B, using packed storage. It improves the solution by iterative refinement, in order to reduce the backward error as much as possible.

2 Specification

SUBROUTINE F07GHF (UPLO, N, NRHS, AP, AFP, B, LDB, X, LDX, FERR, BERR, & WORK, IWORK, INFO)

```
INTEGER N, NRHS, LDB, LDX, IWORK(N), INFO
REAL (KIND=nag_wp) AP(*), AFP(*), B(LDB,*), X(LDX,*), FERR(NRHS), &
BERR(NRHS), WORK(3*N)
CHARACTER(1) UPLO
```

The routine may be called by its LAPACK name *dpprfs*.

3 Description

F07GHF (DPPRFS) returns the backward errors and estimated bounds on the forward errors for the solution of a real symmetric positive definite system of linear equations with multiple right-hand sides AX = B, using packed storage. The routine handles each right-hand side vector (stored as a column of the matrix B) independently, so we describe the function of F07GHF (DPPRFS) in terms of a single right-hand side b and solution x.

Given a computed solution x, the routine computes the *component-wise backward error* β . This is the size of the smallest relative perturbation in each element of A and b such that x is the exact solution of a perturbed system

$$(A + \delta A)x = b + \delta b$$
$$|\delta a_{ij}| \le \beta |a_{ij}| \quad \text{and} \quad |\delta b_i| \le \beta |b_i|.$$

Then the routine estimates a bound for the *component-wise forward error* in the computed solution, defined by:

 $\max_{i} |x_i - \hat{x}_i| / \max_{i} |x_i|$

where \hat{x} is the true solution.

For details of the method, see the F07 Chapter Introduction.

4 References

Golub G H and Van Loan C F (1996) Matrix Computations (3rd Edition) Johns Hopkins University Press, Baltimore

Input

Input

5 Arguments

1: UPLO – CHARACTER(1) Input

On entry: specifies whether the upper or lower triangular part of A is stored and how A is to be factorized.

UPLO = 'U'

The upper triangular part of A is stored and A is factorized as $U^{T}U$, where U is upper triangular.

UPLO = 'L'

The lower triangular part of A is stored and A is factorized as LL^{T} , where L is lower triangular.

Constraint: UPLO = 'U' or 'L'.

2: N – INTEGER

On entry: n, the order of the matrix A. Constraint: $N \ge 0$.

3: NRHS – INTEGER

On entry: r, the number of right-hand sides. Constraint: NRHS ≥ 0 .

- 4: AP(*) REAL (KIND=nag_wp) array Input Note: the dimension of the array AP must be at least max $(1, N \times (N + 1)/2)$. On entry: the n by n original symmetric positive definite matrix A as supplied to F07GDF (DPPTRF).
- 5: $AFP(*) REAL (KIND=nag_wp) array$ **Note:** the dimension of the array AFP must be at least max $(1, N \times (N + 1)/2)$. *On entry*: the Cholesky factor of A stored in packed form, as returned by F07GDF (DPPTRF).
- 6: $B(LDB, *) REAL (KIND=nag_wp) array$ **Note:** the second dimension of the array B must be at least max(1, NRHS). *On entry*: the *n* by *r* right-hand side matrix *B*.
- 7: LDB INTEGER Input On entry: the first dimension of the array B as declared in the (sub)program from which F07GHF (DPPRFS) is called.

Constraint: LDB $\geq \max(1, N)$.

8: X(LDX,*) - REAL (KIND=nag_wp) array Input/Output
 Note: the second dimension of the array X must be at least max(1, NRHS).
 On entry: the n by r solution matrix X, as returned by F07GEF (DPPTRS).
 On exit: the improved solution matrix X.

9:	LDX – INTEGER	Input
	<i>On entry</i> : the first dimension of the array X as declared in the (sub)program from (DPPRFS) is called.	n which F07GHF
	Constraint: $LDX \ge max(1, N)$.	
10:	FERR(NRHS) – REAL (KIND=nag_wp) array	Output
	On exit: $\text{FERR}(j)$ contains an estimated error bound for the <i>j</i> th solution vector column of X, for $j = 1, 2,, r$.	or, that is, the <i>j</i> th
11:	BERR(NRHS) – REAL (KIND=nag_wp) array	Output
	On exit: BERR(j) contains the component-wise backward error bound β for the <i>j</i> th solution vector, that is, the <i>j</i> th column of X, for $j = 1, 2,, r$.	
12:	$WORK(3 \times N) - REAL (KIND=nag_wp) array$	Workspace
13:	IWORK(N) – INTEGER array	Workspace

14: INFO – INTEGER Output

On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = -i, argument *i* had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

The bounds returned in FERR are not rigorous, because they are estimated, not computed exactly; but in practice they almost always overestimate the actual error.

8 Parallelism and Performance

F07GHF (DPPRFS) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07GHF (DPPRFS) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

For each right-hand side, computation of the backward error involves a minimum of $4n^2$ floating-point operations. Each step of iterative refinement involves an additional $6n^2$ operations. At most five steps of iterative refinement are performed, but usually only 1 or 2 steps are required.

Estimating the forward error involves solving a number of systems of linear equations of the form Ax = b; the number is usually 4 or 5 and never more than 11. Each solution involves approximately $2n^2$ operations.

The complex analogue of this routine is F07GVF (ZPPRFS).

10 Example

This example solves the system of equations AX = B using iterative refinement and to compute the forward and backward error bounds, where

$$A = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.18 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.18 & 0.34 & 1.18 \end{pmatrix} \text{ and } B = \begin{pmatrix} 8.70 & 8.30 \\ -13.35 & 2.13 \\ 1.89 & 1.61 \\ -4.14 & 5.00 \end{pmatrix}.$$

Here A is symmetric positive definite, stored in packed form, and must first be factorized by F07GDF (DPPTRF).

10.1 Program Text

Program f07ghfe

```
!
     F07GHF Example Program Text
1
     Mark 26 Release. NAG Copyright 2016.
1
      .. Use Statements ..
     Use nag_library, Only: dpprfs, dpptrf, dpptrs, nag_wp, x04caf
      .. Implicit None Statement ..
1
     Implicit None
!
      .. Parameters ..
     Integer, Parameter
                                       :: nin = 5, nout = 6
!
      .. Local Scalars ..
                                        :: aplen, i, ifail, info, j, ldb, ldx, &
     Integer
                                           n, nrhs
     Character (1)
                                        :: uplo
1
     .. Local Arrays ..
     Real (Kind=nag_wp), Allocatable :: afp(:), ap(:), b(:,:), berr(:),
                                                                                 &
                                          ferr(:), work(:), x(:,:)
     Integer, Allocatable
                                       :: iwork(:)
1
      .. Executable Statements ..
     Write (nout,*) 'FO7GHF Example Program Results'
     Skip heading in data file
1
     Read (nin,*)
     Read (nin,*) n, nrhs
     ldb = n
     ldx = n
     aplen = n*(n+1)/2
     Allocate (afp(aplen),ap(aplen),b(ldb,nrhs),berr(nrhs),ferr(nrhs),
                                                                                &
       work(3*n),x(ldx,n),iwork(n))
     Read A and B from data file, and copy A to AFP and B to X
1
     Read (nin,*) uplo
      If (uplo=='U') Then
       Read (nin,*)((ap(i+j*(j-1)/2),j=i,n),i=1,n)
     Else If (uplo=='L') Then
       Read (nin,*)((ap(i+(2*n-j)*(j-1)/2),j=1,i),i=1,n)
     End If
     Read (nin,*)(b(i,1:nrhs),i=1,n)
     afp(1:aplen) = ap(1:aplen)
     x(1:n, 1:nrhs) = b(1:n, 1:nrhs)
     Factorize A in the array AFP
1
     The NAG name equivalent of dpptrf is f07gdf
!
     Call dpptrf(uplo,n,afp,info)
     Write (nout,*)
     Flush (nout)
     If (info==0) Then
       Compute solution in the array X
1
       The NAG name equivalent of dpptrs is f07gef
1
```

Call dpptrs(uplo,n,nrhs,afp,x,ldx,info)

```
Improve solution, and compute backward errors and
1
!
        estimated bounds on the forward errors
        The NAG name equivalent of dpprfs is f07ghf
1
        Call dpprfs(uplo,n,nrhs,ap,afp,b,ldb,x,ldx,ferr,berr,work,iwork,info)
1
        Print solution
1
        ifail: behaviour on error exit
              =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
1
        ifail = 0
        Call x04caf('General',' ',n,nrhs,x,ldx,'Solution(s)',ifail)
        Write (nout,*)
        Write (nout,*) 'Backward errors (machine-dependent)'
        Write (nout, 99999) berr(1:nrhs)
        Write (nout,*) 'Estimated forward error bounds (machine-dependent)'
        Write (nout,99999) ferr(1:nrhs)
      Else
        Write (nout,*) 'A is not positive definite'
     End If
99999 Format ((3X,1P,7E11.1))
   End Program f07ghfe
```

10.2 Program Data

F07GHF Example Program Data 4 2 :Values of N and NRHS 'L':Value of UPLO 4.16 -3.12 5.03 0.56 -0.83 0.76 -0.10 1.18 0.34 1.18 :End of matrix A 8.30 8.70 -13.35 2.13 1.89 1.61 -4.14 5.00 :End of matrix B

10.3 Program Results

F07GHF Example Program Results

Solution(s) 1 2 1.0000 4.0000 1 -1.0000 3.0000 2 3 2.0000 2.0000 -3.0000 4 1.0000 Backward errors (machine-dependent) 5.1E-17 6.1E-17 Estimated forward error bounds (machine-dependent) 2.3E-14 2.3E-14