

NAG Library Function Document

nag_elliptic_integral_complete_E (s21bjc)

1 Purpose

nag_elliptic_integral_complete_E (s21bjc) returns a value of the classical (Legendre) form of the complete elliptic integral of the second kind.

2 Specification

```
#include <nag.h>
#include <nags.h>
double nag_elliptic_integral_complete_E (double dm, NagError *fail)
```

3 Description

nag_elliptic_integral_complete_E (s21bjc) calculates an approximation to the integral

$$E(m) = \int_0^{\frac{\pi}{2}} (1 - m \sin^2 \theta)^{\frac{1}{2}} d\theta,$$

where $m \leq 1$.

The integral is computed using the symmetrised elliptic integrals of Carlson (Carlson (1979) and Carlson (1988)). The relevant identity is

$$E(m) = R_F(0, 1 - m, 1) - \frac{1}{3}mR_D(0, 1 - m, 1),$$

where R_F is the Carlson symmetrised incomplete elliptic integral of the first kind (see nag_elliptic_integral_rf (s21bbc)) and R_D is the Carlson symmetrised incomplete elliptic integral of the second kind (see nag_elliptic_integral_rd (s21bcc)).

4 References

Abramowitz M and Stegun I A (1972) *Handbook of Mathematical Functions* (3rd Edition) Dover Publications

Carlson B C (1979) Computing elliptic integrals by duplication *Numerische Mathematik* **33** 1–16

Carlson B C (1988) A table of elliptic integrals of the third kind *Math. Comput.* **51** 267–280

5 Arguments

- 1: **dm** – double *Input*
On entry: the argument m of the function.
Constraint: **dm** \leq 1.0.
- 2: **fail** – NagError * *Input/Output*
 The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in How to Use the NAG Library and its Documentation for further information.

NE_REAL

On entry, $\mathbf{dm} = \langle \text{value} \rangle$; the integral is undefined.

Constraint: $\mathbf{dm} \leq 1.0$.

7 Accuracy

In principle `nag_elliptic_integral_complete_E` (s21bjc) is capable of producing full *machine precision*. However round-off errors in internal arithmetic will result in slight loss of accuracy. This loss should never be excessive as the algorithm does not involve any significant amplification of round-off error. It is reasonable to assume that the result is accurate to within a small multiple of the *machine precision*.

8 Parallelism and Performance

`nag_elliptic_integral_complete_E` (s21bjc) is not threaded in any implementation.

9 Further Comments

You should consult the s Chapter Introduction, which shows the relationship between this function and the Carlson definitions of the elliptic integrals. In particular, the relationship between the argument-constraints for both forms becomes clear.

For more information on the algorithms used to compute R_F and R_D , see the function documents for `nag_elliptic_integral_rf` (s21bbc) and `nag_elliptic_integral_rd` (s21bcc), respectively.

10 Example

This example simply generates a small set of nonextreme arguments that are used with the function to produce the table of results.

10.1 Program Text

```
/* nag_elliptic_integral_complete_E (s21bjc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */
/* Pre-processor includes */
```

```

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nags.h>

int main(void)
{
    /*Integer scalar and array declarations */
    Integer exit_status = 0;
    Integer ix;
    /*Double scalar and array declarations */
    double dm, E;
    NagError fail;

    INIT_FAIL(fail);

    printf("%s\n",
           "nag_elliptic_integral_complete_E (s21bjc) Example Program Results");
    printf("\n");
    printf("%s\n", "    dm          nag_elliptic_integral_complete_E");
    printf("\n");
    for (ix = 1; ix <= 3; ix++) {
        dm = ix * 0.250e0;
        /*
         * nag_elliptic_integral_complete_E (s21bjc)
         * Complete elliptic integral of 2nd kind, Legendre form, E(m)
         */
        E = nag_elliptic_integral_complete_E(dm, &fail);
        if (fail.code != NE_NOERROR) {
            printf("Error from "
                  "nag_elliptic_integral_complete_E (s21bjc).\n%s\n",
                  fail.message);
            exit_status = 1;
            goto END;
        }
        printf("%7.2f%12.4f\n", dm, E);
    }

END:

    return exit_status;
}

```

10.2 Program Data

None.

10.3 Program Results

nag_elliptic_integral_complete_E (s21bjc) Example Program Results

dm	nag_elliptic_integral_complete_E
0.25	1.4675
0.50	1.3506
0.75	1.2111
