

# NAG Library Routine Document

## F06TFF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F06TFF performs the matrix-copy operation

$$B \leftarrow A$$

where  $A$  and  $B$  are  $m$  by  $n$  complex general or trapezoidal matrices.

### 2 Specification

```
SUBROUTINE F06TFF (MATRIX, M, N, A, LDA, B, LDB)
  INTEGER          M, N, LDA, LDB
  COMPLEX (KIND=nag_wp) A(LDA,*), B(LDB,*)
  CHARACTER(1)    MATRIX
```

### 3 Description

None.

### 4 References

None.

### 5 Arguments

- |    |   |              |
|----|---|--------------|
| 1: | MATRIX – CHARACTER(1)<br><i>On entry:</i> the matrix type.<br>MATRIX = 'G'<br>General matrix.<br>MATRIX = 'U'<br>Upper trapezoidal matrix (upper triangular if $m = n$ ).<br>MATRIX = 'L'<br>Lower trapezoidal matrix (lower triangular if $m = n$ ).<br><i>Constraint:</i> MATRIX = 'G', 'U' or 'L'. | <i>Input</i> |
| 2: | M – INTEGER<br><i>On entry:</i> $m$ , the number of rows of the matrices $A$ and $B$ .<br><i>Constraint:</i> $M \geq 0$ .   | <i>Input</i> |
| 3: | N – INTEGER<br><i>On entry:</i> $n$ , the number of columns of the matrices $A$ and $B$ .<br><i>Constraint:</i> $N \geq 0$ .  | <i>Input</i> |

4: A(LDA,\*) – COMPLEX (KIND=nag\_wp) array Input

**Note:** the second dimension of the array A must be at least N.

*On entry:* the  $m$  by  $n$  general or trapezoidal matrix  $A$ .

If MATRIX = 'U',  $A$  is upper trapezoidal and the elements of the array below the diagonal are not referenced.

If MATRIX = 'L',  $A$  is lower trapezoidal and the elements of the array above the diagonal are not referenced.

5: LDA – INTEGER Input

*On entry:* the first dimension of the array A as declared in the (sub)program from which F06TFF is called.

*Constraint:*  $LDA \geq \max(1, M)$ .

6: B(LDB,\*) – COMPLEX (KIND=nag\_wp) array Output

**Note:** the second dimension of the array B must be at least N.

*On exit:* the  $m$  by  $n$  general or trapezoidal matrix  $B$ .

If MATRIX = 'U',  $B$  is upper trapezoidal and the elements of the array below the diagonal are not referenced.

If MATRIX = 'L',  $B$  is lower trapezoidal and the elements of the array above the diagonal are not referenced.

7: LDB – INTEGER Input

*On entry:* the first dimension of the array B as declared in the (sub)program from which F06TFF is called.

*Constraint:*  $LDB \geq \max(1, M)$ .

## 6 Error Indicators and Warnings

None.

## 7 Accuracy

Not applicable.

## 8 Parallelism and Performance

F06TFF is not threaded in any implementation.

## 9 Further Comments

None.

## 10 Example

None.

---